



CERTIFICATE

No. U6 133490 0002 Rev. 00

Holder of Certificate: **VoxAura GmbH**
Eschentalweg 5
77948 Friesenheim
GERMANY

Certification Mark:



Product: **Electronic controlgear for LED modules
(LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142255010601

Date, 2026-06-05

(Taylor Yao)



CERTIFICATE

No. U6 133490 0002 Rev. 00

Model(s):

ID4001, 20W;
ID4001, 40W;
ID2001, 20W;
ID2001, 40W;
SD4000, 20W;
SD4000, 40W;
SD2000, 20W;
SD2000, 40W;
ID4001, 60W;
ID2001, 60W;
SD4000, 60W;
SD2000, 60W;
ID4001, 100W;
ID2001, 100W;
SD4000, 100W;
SD2000, 100W;
ID4001, 150W;
SD4000, 150W

Brand Name: VOXAURA

VOXAURA

Parameters:

Rated Input Voltage: 220-240VAC
Rated Frequency: 50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant voltage type
ta: -20 to 45°C
tc: See below table for details

Tested according to:

EN IEC 61347-2-13:2024
EN IEC 61347-1:2024
EN IEC 62384:2020

Production Facility(ies):

105051

CERTIFICATE

No. U6 133490 0002 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (A) (max.)	U _{out} (VDC)	P _{rated} (W) (max.)	tc (°C)
ID4001, 20W	0.15	24	0.83	25	20	80
ID4001, 40W	0.30	24	1.67	25	40	80
ID2001, 20W	0.15	12	1.67	13	20	80
ID2001, 40W	0.30	12	3.34	13	40	80
SD4000, 20W	0.15	24	0.83	25	20	80
SD4000, 40W	0.30	24	1.67	25	40	80
SD2000, 20W	0.15	12	1.67	13	20	80
SD2000, 40W	0.30	12	3.34	13	40	80
ID4001, 60W	0.4	24	2.5	25	60	90
ID2001, 60W	0.4	12	5.0	13	60	90
SD4000, 60W	0.4	24	2.5	25	60	90
SD2000, 60W	0.4	12	5.0	13	60	90
ID4001, 100W	0.65	24	4.17	25	100	80
ID2001, 100W	0.65	12	8.33	13	100	80
SD4000, 100W	0.65	24	4.17	25	100	80
SD2000, 100W	0.65	12	8.33	13	100	80
ID4001, 150W	0.9	24	6.25	25	150	80
SD4000, 150W	0.9	24	6.25	25	150	80